

Product name	: BENMAN ACRYLIC COLOR MATTE	
Colour	: RAL 9005 Matte Black	RAL 9010 Matte White
Reference number	: 28 528	28 529

Product description

High quality lacquer for professional use. To treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Product characteristics

- Fast drying
- Excellent coverage and filling property
- Lasting colour and lasting gloss
- Scratch free and shock proof
- Resistant to weather influences
- Rust preventive
- UV resistant and non-fading
- Good adhesion

Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Acrylic resin
VOC-content	: Approximately 88% w/w
Solid content	: Approximately 12% w/w
Coverage	: 1,25 to 1,75 m ²
Dust dry	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 2 hours
Heat resistant	: up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease.
Remove loose old lacquer and rust and sand the surface.
Apply a layer of product suitable for the surface. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature.
Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample.
Distance to the surface to be treated approximately 25 to 30 centimeters.

Apply the product in several thin layers. Before applying the next layer, again shake the can.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.