

Product name	:	BENMAN FLUORESCENT			
Colour	:	Red-Orange	Pink	Yellow	Green
Reference number	:	28 532	28 533	28 534	28 535

Product description

High quality fluorescent lacquer to treat surfaces, treated and untreated, of metal, concrete, stone, wood, glass and various types of plastic.

Product characteristics

Fast drying
Fluorescent
Excellent adhesion

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Nitro-cellulose binder
Colour	:	Red-Orange, Pink, Yellow, Green
VOC-content	:	Approximately 87% w/w
Solid content	:	Approximately 13% w/w
Gloss	:	Satin matt
Coverage	:	1,25 to 1,75 m ²
Dust dry	:	After 5 to 10 minutes
Tack free	:	After 10 to 20 minutes
Hardened/re-sprayable	:	After 2 hours
Heat resistant	:	up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. In order to achieve the best fluorescent effect, apply a layer of white primer. When treating surfaces of plastic, first apply a layer of plastic primer before applying the white primer. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.

Apply the product in several thin layers. Before applying the next layer, again shake the can.

Recommendation:

In order to improve the resistance to UV and weather influences, apply a finishing coat of acrylic clear varnish.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.