

Product name	:	BENMAN HAMMER FINISH					
Colour	:	Blue	Green	Silver	Grey	Gold	Antracite
Reference number	:	28555	28556	28557	28558	28559	28560

Product description

High quality lacquer with hammered effect to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Product characteristics

Fast drying
Good coverage
Scratch free and shock proof
Resistant to petrol, chemicals, thinned cleaners and weather influences

Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Alkyd resin
Colour	: Blue, Green, Silver, Grey, Gold, Anthracite
VOC-content	: Approximately 82% w/w
Solid content	: Approximately 18% w/w
Coverage	: 1,25 to 1,75 m ²
Dust dry	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 24 hours
Heat resistant	: up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of primer suitable for the surface. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.

Apply a thin first layer and after several minutes apply a finishing coat. Before applying the next layer, again shake the can.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.