

**Product name** : BENMAN VASELINE SPRAY  
**Reference number** : 28 569

### Product description

High quality transparent, universal lubricant and preservative.

### Applications

Battery poles  
Audio controls  
Fasteners (screws, bolts, nuts and nails)  
Antennas  
Electrical connections  
Protection for ultra light material (ultra light planes, wind turbines)

### Product characteristics

Water-repellent  
Excellent adhesion  
Prevents wear and sticking  
Can be used in the food industry  
Resistant to weather influences  
Resistant to weak acids and bases  
Excellent corrosion prevention  
Misty spray pattern

### Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Vaseline
Colour	: White
Scent	: Characteristic
VOC-content	: Approximately 85% w/w
Relative density at 20°C	: 0,89 g/ml
Yield	: 1,11 g /sec
Vapour pressure at 20°C	: 3 to 4 bar
4 Ball EP-test (ASTM D 2596)	: 3136 N
4 Ball Wear-test (ASTM D 2266)	: <0,4mm
Drop point	: 42°C - 60°C
Temperature resistant	: -30°C to +160°C
ph-value	: Neutral



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The can should have room temperature.  
Best application temperature 5 to 30°C.  
Before use, shake the can.

Apply product in a thin layer.  
Optimum lubrication is obtained after evaporation of the solvent.