

Product name : BENMAN SILICONE SPRAY
Reference number : 28 583

Product description

High quality silicone spray to lubricate and protect plastic or rubber parts.

Applications

Door rubbers	Creaking plastic parts
Dashboards	Bumpers
Sunshine roofs	Rails (caravan, blinds)
Sliding doors	Saw blades
Remove agents for moulds	

Product characteristics

Excellent adhesion
Water repellent
Prevents freezing and drying out of rubber parts
Prevents creaking and squeaking of plastic parts
Outstanding mechanical and thermal stability
Resistant to weather influences
Resistant to weak acids and bases
Directed jetspray



Physical and Chemical Characteristics

Contents	: 400 ml
Basis	: Polydimethylsiloxaan
VOC-content	: Approximately 88% w/w
Colour	: Transparent light brown
Scent	: Characteristic
Relative density at 20°C	: 0,72 g/ml
Vapour pressure at 20°C	: 3 to 4 bar
Refractive Index at 25°C	: 1,403
Disruptive strength	: 14 kv/mm at a temperature of 20°C
Resistance	: 4×10^{15} Ohm/cm
Temperature resistant	: -50°C to + 200°C
ph-value	: Neutral

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The can should have room temperature.
Before application temperature 5 to 30°C.
Before use, shake the can.

Apply product in a thin layer.
Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).