

Product name : BENMAN PLASTIC PRIMER
Reference number : 28 617

Product description

High quality, fast drying plastic primer to treat surfaces, treated and untreated, of several types of plastic.

Product characteristics

Fast drying
Excellent adhesion
Re-sprayable with all lacquer systems
Not suitable for treatment of PE.

Physical and Chemical Characteristics

Contents : 400 ml
Base : Polyolefine resin
VOC-content : Approximately 99% w/w
Colour : Transparent
Solid content : Approximately 1% w/w
Coverage : 2 to 3 m²
Re-sprayable : After 10 to 15 minutes



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. When desired, slightly sand the surface, grain 600.

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the product in maximum two (2) thin layers.

After drying, without sanding, re-sprayable with all lacquer systems.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.