

<b>Product name</b>	: <b>BENMAN ALU</b>	
<b>Colour</b>	: <b>RAL 9016 White</b>	<b>RAL 8014 Brown</b>
<b>Reference number</b>	: <b>33 882</b>	<b>33 985</b>

### Product description

High quality Alu spray for professional use. To repair and treat surfaces of aluminium.

### Product characteristics

Fast drying  
Lasting colour and lasting gloss  
Scratch free and shock proof  
Resistant to weather influences  
UV resistant and non-fading  
Good adhesion

### Physical and Chemical Characteristics

Contents	: 200 ml
Base	: Acrylic resin
Colour	: White RAL 9016, Brown RAL 8014
VOC-content	: Approximately 88% w/w
Solid content	: Approximately 12% w/w
Coverage	: 0,50 to 1,00 m <sup>2</sup>
Dust dry	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 2 hours
Heat resistant	: up to 110°C



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

#### Pre Treatment

The surface should be clean, dry and free of grease.  
Remove loose old lacquer and rust and sand the surface.

#### Treatment

The surface should be clean, dry and free of grease. The can should have room temperature.  
Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetres.

Apply the product in several thin layers. Before applying the next layer, again shake the can.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

**The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.**