

Product name : BENMAN BACKLIGHT BLACK SPRAY
Reference number : 35 392

Product description

High quality transparent lacquer to highlight backlights.

Product characteristics

Lasting gloss
Scratch free and shock proof
Resistant to petrol, chemicals and weather influences
Good adhesion
Not suitable to treat surfaces of polycarbonate

Physical and Chemical Characteristics

Contents	: 400 ml
Basis	: Alkyd resin
VOC-content	: Approximately 90% w/w
Solid content	: Approximately 10% w/w
Gloss	: High gloss 90 at an angle of 60°
Coverage	: 2 to 4 backlights Approximately 8 backlights
Dust dry	: After 30 minutes
Tack free	: After 2 hours
Hardened/Re-spray able	: After 4 hours



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface must be clean, dry and free of grease

Treatment

The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.

Apply the product in several thin layers, till the desired result has been achieved. Before applying the next layer, again shake the can.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.